

# Lightweight Systems

## LED 12"

### 12" LED On-Camera Unit

|                       |   |
|-----------------------|---|
| <b>Brightness:</b>    | 1000 nits   |
| <b>Weight:</b>        | 2.95kg (6.5lb)<br>Monitor only<br>7.4kg (16.3lb)<br>Typical all up weight |
| <b>Reading Range:</b> | 2 meters - 12 feet  |
| <b>Power:</b>         | 12V DC 34 watts   |
| <b>Power Supply:</b>  | Internal PSU, 90 to 260V AC,<br>160V DC or 12V DC                         |
| <b>Video:</b>         | Autosensing PAL/NTSC, VGA,<br>HD/SD-SDI (OPTION)                          |

“ Autoscript has always responded to our needs quickly and efficiently, which is largely why we have had a relationship that has been built up and maintained over a period of 20 or so years.

**Steve Luck**  
SENIOR TEAM LEADER, ITN STUDIOS



## Miniscript 5.6"

**A 440g (1lb), on-camera 5.6" LED backlit flat screen monitor for handheld cameras in live and studio-based production.**

Features include:

- > Very low weight and power consumption
- > Allows presenters to move freely around set
- > Low mounted monitor so talent doesn't appear to be reading over the camera
- > Large enough for camera operator to stand 6 feet (2m) away from talent
- > Rugged all-metal case
- > Professional connectors
- > Scan reverse switch

## LED 8"

**A High Bright LED on-camera prompter in an 8" screen size providing:**

- > 1700 nits of brightness
- > 30% less power draw and 20% reduction in weight from previous product
- > Outstanding performance under daylight conditions
- > Composite and VGA inputs
- > Built in Tally light and illuminated control panel for easy viewing
- > 12V DC accessory power outlet and mounting for TallyPlus and CuePlus



### 8" LED On-Camera Unit

|                       |  |
|-----------------------|--|
| <b>Brightness:</b>    | 1700 nits  |
| <b>Weight:</b>        | 1.2kg (2.10lb)<br>Monitor only<br>3.5kg (7.8lb)<br>Typical all up weight |
| <b>Reading Range:</b> | 3m (9ft)   |
| <b>Power:</b>         | 12V DC 1.5A 18W  |
| <b>Power Supply:</b>  | External 12V DC  |
| <b>Video:</b>         | PAL/NTSC (2), VGA  |

### 5.6" On-Camera Unit Prompter

|                       |                   |
|-----------------------|-------------------|
| <b>Brightness:</b>    | 500 nits          |
| <b>Weight:</b>        | 440g (1lb)        |
| <b>Reading Range:</b> | 2 metres - 6 feet |
| <b>Power:</b>         | 12V DC 3 watts    |
| <b>Power Supply:</b>  | 12V DC            |
| <b>Video:</b>         | PAL/NTSC          |

